



# APPENDIX D

## AIR QUALITY



This page is intentionally blank.

**ACRONYMS, ABBREVIATIONS, AND SYMBOLS**

<b>µg/m<sup>3</sup></b>	micrograms per cubic meter	<b>PM<sub>10</sub></b>	particulate matter with an aerodynamic diameter less than or equal to 10 microns
<b>ACAM</b>	Air Conformity Applicability Model	<b>PM<sub>2.5</sub></b>	particulate matter with an aerodynamic diameter less than or equal to 2.5 microns
<b>AGL</b>	above ground level	<b>ppm</b>	parts per million
<b>APU</b>	auxiliary power unit	<b>ROI</b>	region of influence
<b>BAPC</b>	Bureau of Air Pollution Control	<b>SO<sub>2</sub></b>	sulfur dioxide
<b>CAA</b>	Clean Air Act	<b>TGO</b>	touch and go
<b>CEQ</b>	Council on Environmental Quality	<b>TP</b>	target practice
<b>CFR</b>	Code of Federal Regulations	<b>U.S.</b>	United States
<b>CH<sub>4</sub></b>	methane	<b>EPA</b>	U.S. Environmental Protection Agency
<b>CO</b>	carbon monoxide	<b>VMT</b>	volume of miles traveled
<b>CO<sub>2</sub></b>	carbon dioxide	<b>VOC</b>	volatile organic compound
<b>CO<sub>2</sub>-e</b>	carbon dioxide equivalents	<b>yr</b>	year
<b>CY</b>	calendar year		
<b>EAC</b>	early action compact		
<b>ETR</b>	engine thrust ratio		
<b>FFR</b>	fuel flow rate		
<b>GBU</b>	guided bomb unit		
<b>GHG</b>	greenhouse gas		
<b>GOV</b>	government-owned vehicle		
<b>HAP</b>	hazardous air pollutant		
<b>lb</b>	pound		
<b>mg/m<sup>3</sup></b>	milligrams per cubic meter		
<b>mm</b>	millimeter		
<b>N<sub>2</sub>O</b>	nitrous oxide		
<b>NAA</b>	No Action Alternative		
<b>NAAQS</b>	National Ambient Air Quality Standards		
<b>NDEP</b>	Nevada Division of Environmental Protection		
<b>NEI</b>	National Emissions Inventory		
<b>NEW</b>	net explosive weight		
<b>NO<sub>2</sub></b>	nitrogen dioxide		
<b>NO<sub>x</sub></b>	nitrogen oxides		
<b>O<sub>3</sub></b>	ozone		
<b>Pb</b>	lead		

This page is intentionally blank.

---

1 **D.1 AIR QUALITY**

2 This appendix presents an overview of the Clean Air Act (CAA) and the state of Nevada air  
3 quality program. The appendix also discusses emissions factor development and  
4 calculations, including the assumptions used for the air quality analyses presented in the  
5 Air Quality sections.

6 **D.1.1 Air Quality Program Overview**

7 In order to protect public health and welfare, the U.S. Environmental Protection Agency  
8 (EPA) has developed numerical concentration-based standards, or National Ambient Air  
9 Quality Standards (NAAQS), for six “criteria” pollutants (based on health-related criteria)  
10 under the provisions of the CAA Amendments of 1970. There are two kinds of NAAQS:  
11 primary and secondary standards. Primary standards prescribe the maximum permissible  
12 concentration in the ambient air to protect public health, including the health of “sensitive”  
13 populations such as asthmatics, children, and the elderly. Secondary standards prescribe  
14 the maximum concentration or level of air quality required to protect public welfare,  
15 including protection against decreased visibility, damage to animals, crops, vegetation, and  
16 buildings (40 Code of Federal Regulations [CFR] 50).

17 The CAA gives states the authority to establish air quality rules and regulations. These  
18 rules and regulations must be equivalent to, or more stringent than, the federal program.  
19 The Nevada Division of Environmental Protection’s (NDEP) Bureau of Air Pollution Control  
20 (BAPC) administers the state’s air pollution control program under the authority of the  
21 Nevada Revised Statutes (NRS) 445B.100 through 445B.825, inclusive, and NRS  
22 486A.010 through 486A.180, inclusive. Washoe and Clark counties administer air quality  
23 programs within each of their respective jurisdictions. The Clark County Department of Air  
24 Quality is the air pollution control agency for all of Clark County, Nevada.

25 The Nevada Ambient Air Quality Standards differ from the EPA’s NAAQS for several  
26 pollutants and are included in Table D-1. Summary of Nevada and National Ambient Air  
27 Quality Standards. However, in accordance with Nevada Administrative Code  
28 445B.22097, Nevada standards are only to be used “in considering whether to issue a  
29 permit for a stationary source and shall ensure that the stationary source will not cause the  
30 Nevada standards to be exceeded in areas where the general public has access” and  
31 further states that the NAAQS are to be used in determinations of attainment or  
32 nonattainment.

33 Based on measured ambient air pollutant concentrations, the EPA designates areas of the  
34 United States as having air quality better than (attainment) the NAAQS, worse than  
35 (nonattainment) the NAAQS, and unclassifiable. The areas that cannot be classified (on  
36 the basis of available information) as meeting or not meeting the NAAQS for a particular  
37 pollutant are “unclassifiable” and are treated as attainment until proven otherwise.  
38 Attainment areas can be further classified as “maintenance” areas, which are areas  
39 previously classified as nonattainment but where air pollutant concentrations have been  
40 successfully reduced to below the standard. Maintenance areas are under special

1 maintenance plans and must operate under some of the nonattainment area plans to  
 2 ensure compliance with the NAAQS. Clark, Lincoln, and Nye counties are in compliance  
 3 with the NAAQS. Therefore, every county within the project region of influence (ROI) is  
 4 classified as being in attainment.

5 A general conformity analysis is required to be conducted for areas designated as  
 6 nonattainment or maintenance of the NAAQS if the action's direct and indirect emissions  
 7 have a potential to emit one or more of the six criteria pollutants at or above concentrations  
 8 standards shown in Table D-1 or the *de minimis* emission rate thresholds in Table D-2 or  
 9 Table D-3.

**Table D-1. Summary of Nevada and National Ambient Air Quality Standards**

Pollutant	Averaging Time	NEVADA STANDARDS <sup>a</sup>		NATIONAL STANDARDS <sup>b</sup>		
		Concentration <sup>c</sup>	Method <sup>d</sup>	Primary <sup>c, e</sup>	Secondary <sup>c, f</sup>	Method <sup>d</sup>
Ozone	8 hours	0.070 ppm	Chemi-luminescence	0.070 ppm	Same as primary	Chemi-luminescence
Ozone-Lake Tahoe Basin, #90	1 hour	0.10 ppm(195 µg/m <sup>3</sup> )	Ultraviolet absorption	--	--	--
Carbon monoxide less than 5,000' above mean sea level	8 hours	9 ppm(10,500 µg/m <sup>3</sup> )	Nondispersive infrared photometry	9 ppm(10 mg/m <sup>3</sup> )	None	Nondispersive infrared photometry
Carbon monoxide at or greater than 5,000' above mean sea level		6 ppm(7,000 µg/m <sup>3</sup> )				
Carbon monoxide at any elevation	1 hour	35 ppm(40,500 µg/m <sup>3</sup> )		35 ppm(40 mg/m <sup>3</sup> )		
Nitrogen dioxide	Annual arithmetic mean	0.053 ppm(100 µg/m <sup>3</sup> )	Gas phase chemi-luminescence	53 ppb <sup>g</sup>	Same as primary	Gas phase chemi-luminescence
	1 hour	100 ppb	--	100 ppb	None	
Sulfur dioxide	Annual arithmetic mean	0.030 ppm(80 µg/m <sup>3</sup> )	Ultraviolet fluorescence	0.03 ppm <sup>h</sup> (1971 standard)	None	Spectro-photometry (Pararosaniline method)
	24 hours	0.14 ppm(365 µg/m <sup>3</sup> )		0.14 ppm <sup>h</sup> (1971 standard)		
	3 hours	0.5 ppm(1,300 µg/m <sup>3</sup> )		None	0.5 ppm	
	1 hour	75 ppb	--	75 ppb	None	
Particulate matter as PM <sub>10</sub>	24 hours	150 µg/m <sup>3</sup>	High volume PM <sub>10</sub> sampling	150 µg/m <sup>3</sup>	Same as primary	High or low volume PM <sub>10</sub> sampling

**Table D-1. Summary of Nevada and National Ambient Air Quality Standards**

Pollutant	Averaging Time	NEVADA STANDARDS <sup>a</sup>		NATIONAL STANDARDS <sup>b</sup>		
		Concentration <sup>c</sup>	Method <sup>d</sup>	Primary <sup>c, e</sup>	Secondary <sup>c, f</sup>	Method <sup>d</sup>
	Annual arithmetic mean	12.0 µg/m <sup>3</sup>	--	12.0 µg/m <sup>3</sup>	Same as primary	Low volume PM <sub>2.5</sub> sampling
as PM <sub>2.5</sub>	24 hours	35 µg/m <sup>3</sup>	--	35 µg/m <sup>3</sup>	Same as primary	
Lead (Pb)	Rolling 3 mo. average	0.15 µg/m <sup>3</sup>	High volume sampling, acid extraction and atomic absorption spectrometry	0.15 µg/m <sup>3</sup>	Same as primary	High volume sampling, acid extraction and atomic absorption spectrometry
Hydrogen sulfide	1 hour	0.08 ppm (112 µg/m <sup>3</sup> ) <sup>i</sup>	Ultraviolet fluorescence	--	--	--

- <sup>a</sup> The Director shall use the Nevada standards in considering whether to issue a permit for a stationary source and shall ensure that the stationary source will not cause the Nevada standards to be exceeded in areas where the general public has access. For the 2006 particulate matter as PM<sub>2.5</sub> 24-hour and annual standards, the 2010 nitrogen dioxide 1-hour standard and the 2010 sulfur dioxide 1-hour standard, the Director shall use the form of the standards set forth in 40 CFR 50.11, 50.13 and 50.17, as those provisions existed on June 23, 2014, to ensure that the Nevada standard is no more stringent than the National standard in determining whether the stationary source will comply with the Nevada standards in areas where the general public has access.
- <sup>b</sup> The National standards are used in determinations of attainment or nonattainment. The form of a National standard is the criteria which must be satisfied for each respective concentration level of a standard for the purposes of attainment. The form for each National standard is set forth in 40 CFR Part 50 and may be viewed at <http://www.epa.gov/air/criteria.html>.
- <sup>c</sup> Where applicable and except as otherwise described in Note G, concentration is expressed first in units in which it was adopted. Measurements of air quality that are expressed as mass per unit volume, such as micrograms per cubic meter, must be corrected to a reference temperature of 25 degrees Centigrade and a reference pressure of 760 mm of Hg (1,013.2 millibars), except measurements of particulate matter as PM<sub>2.5</sub> and lead (Pb), which are calculated in micrograms per cubic meter at local conditions; "ppb" in this table refers to parts per billion by volume, or nanomoles of regulated air pollutant per mole of gas; "ppm" refers to parts per million by volume, or micromoles of regulated air pollutant per mole of gas; "µg/m<sup>3</sup>" refers to micrograms per cubic meter.
- <sup>d</sup> Reference method as described by the EPA. Any reference method specified in accordance with 40 CFR Part 50 or any reference method or equivalent method designated in accordance with 40 CFR Part 53 may be substituted.
- <sup>e</sup> National primary standards are the levels of air quality necessary, with an adequate margin of safety, to protect the public health.
- <sup>f</sup> National secondary standards are the levels of air quality necessary to protect the public welfare from any known or anticipated adverse effects of a regulated air pollutant.
- <sup>g</sup> The official National annual standard for nitrogen dioxide is 0.053 ppm. The National annual standard is identified in this table in equivalent units of parts per billion for the purpose of simplifying its comparison with the National 1-hour standard which is also identified in parts per billion.
- <sup>h</sup> The 1971 National sulfur dioxide standards remain in effect for an area until 1 year after the area is designated for the 2010 National sulfur dioxide standard, except that in an area designated nonattainment for the 1971 National sulfur dioxide standards, the 1971 standards remain in effect until an implementation plan to attain or maintain the 2010 National sulfur dioxide standards is approved.
- <sup>i</sup> The ambient air quality standard for hydrogen sulfide does not include naturally occurring background concentrations.
1. These standards of quality for ambient air are minimum goals, and it is the intent of the Commission to protect the existing quality of Nevada's air to the extent that it is economically and technically feasible. [Environmental Comm'n, Air Quality Reg. §§ 12.1-12.1.6, eff. 11-7-75; A and renumbered as § 12.1, 12-4-76; A 12-15-77; 8-28-79; §§ 12.2-12.4, eff. 11-7-75; § 12.5, eff. 12-4-76; A 8-28-79] — (NAC A 10-19-83; 9-5-84; 12-26-91; 10-30-95; R103-02, 12-17-2002; R198-03, 4-26-2004; R038-12, 9-14-2012; R042-13, 12-23-2013; R145-13, 6-23-2014; R027-15, 10-27-2015)

**Table D-2. Emission Rates for Criteria Pollutants in Nonattainment Areas<sup>1</sup>**

Pollutant	Emission Rate (tons/year)
<b>Ozone (VOCs or NO<sub>x</sub>)</b>	
Serious nonattainment areas	50
Severe nonattainment areas	25
Extreme nonattainment areas	10
Other ozone nonattainment areas outside an ozone transport region	100
<b>Marginal and moderate nonattainment areas inside an ozone transport region</b>	
VOCs	50
NO <sub>x</sub>	100
CO: All nonattainment areas	100
SO <sub>2</sub> or NO <sub>2</sub> : All nonattainment areas	100
<b>PM<sub>10</sub></b>	
Moderate nonattainment areas	100
Serious nonattainment areas	70
<b>PM<sub>2.5</sub></b>	
Direct emissions	100
SO <sub>2</sub>	100
NO <sub>x</sub> (unless determined not to be a significant precursor)	100
VOCs or ammonia (if determined to be significant precursors)	100
Pb: All nonattainment areas	25

Source: EPA, 2006

CO = carbon monoxide; NO<sub>2</sub> = nitrogen dioxide; NO<sub>x</sub> = nitrogen oxides; VOC = volatile organic compound; Pb = lead; PM<sub>2.5</sub> = particulate matter with a diameter less than or equal to 2.5 microns; PM<sub>10</sub> = particulate matter with a diameter less than or equal to 10 microns; SO<sub>2</sub> = sulfur dioxide

1. *De minimis* threshold levels for conformity applicability analysis.

1 **Table D-3. Emission Rates for Criteria Pollutants in Attainment (Maintenance) Areas<sup>1</sup>**

Pollutant	Emission Rate (tons/year)
Ozone (NO <sub>x</sub> , SO <sub>2</sub> , or NO <sub>2</sub> ): All maintenance areas	100
<b>Ozone (VOCs)</b>	
Maintenance areas inside an ozone transport region	50
Maintenance areas outside an ozone transport region	100
CO: All maintenance areas	100
PM <sub>10</sub> : All maintenance areas	100
<b>PM<sub>2.5</sub></b>	
Direct emissions	100
SO <sub>2</sub>	100
NO <sub>x</sub> (unless determined not to be a significant precursor)	100
VOCs or ammonia (if determined to be significant precursors)	100
Pb: All maintenance areas	25

Source: EPA, 2006

CO = carbon monoxide; NO<sub>x</sub> = nitrogen oxides; VOC = volatile organic compound; Pb = lead; PM<sub>2.5</sub> = particulate matter with a diameter less than or equal to 2.5 microns; PM<sub>10</sub> = particulate matter with a diameter less than or equal to 10 microns; SO<sub>2</sub> = sulfur dioxide

1. *De minimis* threshold levels for conformity applicability analysis.

- 2 Each state is required to develop a State Implementation Plan (SIP) that sets forth how  
 3 CAA provisions will be imposed within the state. The SIP is the primary means for the  
 4 implementation, maintenance, and enforcement of the measures needed to attain and  
 5 maintain the NAAQS within each state and includes control measures, emissions  
 6 limitations, and other provisions required to attain and maintain the ambient air quality  
 7 standards. The purpose of the SIP is twofold. First, it must provide a control strategy that



1 will result in the attainment and maintenance of the NAAQS. Second, it must demonstrate  
 2 that progress is being made in attaining the standards in each nonattainment area. The  
 3 State of Nevada last revised the SIP *Nevada Revised Statutes and Regulatory Elements:  
 4 Air Pollution* and on November 11 and 28, 2012, respectively (NDEP, 2012a, 2012b).

5 In attainment areas, major new or modified stationary sources of air emissions on and in  
 6 the area are subject to Prevention of Significant Deterioration (PSD) review to ensure that  
 7 these sources are constructed without causing significant adverse deterioration of the  
 8 clean air in the area. A major new source is defined as one that has the potential to emit  
 9 any pollutant regulated under the CAA in amounts equal to or exceeding specific major  
 10 source thresholds, that is, 100 or 250 tons/year based on the source's industrial category.  
 11 A major modification is a physical change or change in the method of operation at an  
 12 existing major source that causes a significant "net emissions increase" at that source of  
 13 any regulated pollutant. Table D-4 lists the PSD significant emissions rate thresholds for  
 14 selected criteria pollutants (EPA, 1990).

**Table D-4. Criteria Pollutant Significant Emissions Rate  
 Increases Under PSD Regulations**

Pollutant	Significant Emissions Rate (tons/year)
PM <sub>10</sub>	15
PM <sub>2.5</sub>	10
Total suspended particulates	25
SO <sub>2</sub>	40
NO <sub>x</sub>	40
Ozone (VOCs)	40
CO	100

Source: Title 40 CFR Part 51

CO = carbon monoxide; NO<sub>x</sub> = nitrogen oxides; VOC = volatile organic compound; Pb = lead; PM<sub>2.5</sub>  
 = particulate matter with a diameter less than or equal to 2.5 microns; PM<sub>10</sub> = particulate matter  
 with a diameter less than or equal to 10 microns; PSD = Prevention of Significant Deterioration;  
 SO<sub>2</sub> = sulfur dioxide; VOC = volatile organic compound

15 The goals of the PSD program are to (1) ensure economic growth while preserving existing  
 16 air quality; (2) protect public health and welfare from adverse effects that might occur even  
 17 at pollutant levels better than the NAAQS; and (3) preserve, protect, and enhance the air  
 18 quality in areas of special natural recreational, scenic, or historic value, such as national  
 19 parks and wilderness areas. Sources subject to PSD review are required by the CAA to  
 20 obtain a permit before commencing construction. The permit process requires an  
 21 extensive review of all other major sources within a 50-mile radius and all Class I areas  
 22 within a 62-mile radius of the facility. Emissions from any new or modified source must be  
 23 controlled using best available control technology. The air quality, in combination with  
 24 other PSD sources in the area, must not exceed the maximum allowable incremental  
 25 increase identified in Table D-5. National parks and wilderness areas are designated as  
 26 Class I areas, where any appreciable deterioration in air quality is considered significant.  
 27 Class II areas are those where moderate, well-controlled industrial growth could be  
 28 permitted. Class III areas allow for greater industrial development.

**Table D-5. Federal Allowable Pollutant Concentration Increases Under PSD Regulations**

Pollutant	Averaging Time	Maximum Allowable Concentration ( $\mu\text{g}/\text{m}^3$ )		
		Class I	Class II	Class III
PM <sub>10</sub>	Annual	4	17	34
	24-hour	8	30	60
SO <sub>2</sub>	Annual	2	20	40
	24-hour	5	91	182
	3-hour	25	512	700
NO <sub>2</sub>	Annual	2.5	25	50

Source: Title 40 CFR Part 51

NO<sub>2</sub> = nitrogen dioxide; PM<sub>10</sub> = particulate matter with a diameter less than or equal to 10 microns; PSD = Prevention of Significant Deterioration; SO<sub>2</sub> = sulfur dioxide;  $\mu\text{g}/\text{m}^3$  = micrograms per cubic meter

- 1 The Nevada Ambient Air Quality Monitoring Program of the Bureau of Air Quality Planning  
2 operates an ambient air quality monitoring network of gaseous and particulate pollutant  
3 monitors throughout rural Nevada, except those areas in Washoe and Clark  
4 County. Washoe and Clark County operate and maintain monitoring networks separate from  
5 the State and publish their findings independently (NDEP, 2016). The air quality is  
6 monitored for carbon monoxide, lead, nitrogen dioxide, ozone, and particulate matter. The  
7 monitors tend to be concentrated in areas with the largest population densities. Not all  
8 pollutants are monitored in all areas. The air quality monitoring network is used to identify  
9 areas where the ambient air quality standards are being violated and plans are needed to  
10 reduce pollutant concentration levels to be in attainment with the standards. Also included  
11 are areas where the ambient standards are being met, but plans are necessary to ensure  
12 maintenance of acceptable levels of air quality in the face of anticipated population or  
13 industrial growth.
- 14 The end result of this attainment/maintenance analysis is the development of local and  
15 statewide strategies for controlling emissions of criteria air pollutants from stationary and  
16 mobile sources. The first step in this process is the annual compilation of the ambient air  
17 monitoring results, and the second step is the analysis of the monitoring data for general  
18 air quality, exceedances of air quality standards, and pollutant trends.
- 19 The Nevada Air Pollution Control Program (NAPCP) currently operates monitors in Carson  
20 City, Gardnerville, Stateline, Fernley, Fallon, Elko, and Pahrump. The number of  
21 monitoring sites and their locations vary from year to year due to special purpose  
22 monitoring, temporary monitoring, and closing sites that are no longer needed. Due to the  
23 unique shape and wind patterns in the Las Vegas Valley, high concentration levels occur  
24 in different areas for the different pollutants. For example, CO occurs on calm cold days in  
25 the lowest (and eastern) part of the valley. In addition, ozone occurs on hot sunny days in  
26 the northwest and at higher elevations. Therefore, monitoring sites measure different  
27 pollutants based on their location within the valley (Clark County, 2016). Over the years  
28 of record, the general trend has been decreasing for all criteria pollutants and remaining  
29 below the NAAQS (NDEP, 2011).

## 1 D.1.2 Project Calculations

### 2 D.1.2.1 Methodology

3 In order to evaluate air emissions and their impact on the overall ROI, the emissions  
4 associated with the Proposed Action activities were evaluated in accordance with the  
5 tiered approach outlined in the *Air Force Air Quality Environmental Impact Analysis*  
6 *Process (EIAP) Guide – Fundamentals, Volume I and Volume II – Advanced*  
7 *Assessments*. The first step was to conduct an assessment to determine if the action was  
8 exempt for air quality analysis. The Proposed Action was not subject to any categorical  
9 exclusions or General Conformity exemptions. Since the Proposed Action is not subject to  
10 any exemptions under Tier I, a quantitative assessment (Tier II) was completed. The Tier  
11 II assessment requires a formal evaluation of air impacts based on a quantitative net  
12 change emission inventory of the annual net total direct and indirect emissions of  
13 pollutants of concern. It should be noted that in the case of the NTTR Proposed Action,  
14 there were not any net emissions realized.

15 Air quality impacts were evaluated quantitatively based on a two-pronged approach.  
16 Potential impacts to air quality were first identified as the total emissions of any primary  
17 pollutant that equals 250 tons per year for that pollutant based on the federal New Source  
18 Review/PSD major stationary source threshold. In addition to primary pollutants,  
19 greenhouse gases (GHGs) were compared to an indicator level of 75,000 tons of GHGs.  
20 This established a first-level indicator of potential significance for both primary pollutants  
21 and GHGs.

22 However, since the majority of the emissions related to the Proposed Action and  
23 alternatives would result from activities associated with mobile sources, a second-level  
24 indicator was deemed appropriate. Consequently, if the evaluation showed that the first-  
25 level indicators for primary pollutants and GHGs would be exceeded, each pollutant was  
26 evaluated and compared with the total ROI emissions (Lincoln, Clarke, and Nye Counties)  
27 on a pollutant-by-pollutant basis against the ROI's 2014 National Emissions Inventory  
28 data.

29 Potential impacts to air quality are evaluated with respect to the extent, context, and  
30 intensity of the impact in relation to relevant regulations, guidelines, and scientific  
31 documentation. The Council on Environmental Quality (CEQ) defines significance in terms  
32 of context and intensity in 40 CFR 1508.27. This requires that the significance of the  
33 action must be analyzed with respect to the setting of the Proposed Action and based  
34 relative to the severity of the impact. The CEQ National Environmental Policy Act  
35 Regulations (40 CFR 1508.27(b)) provide 10 key factors to consider in determining an  
36 impact's intensity.

37 Intensity refers to the severity of impact. Responsible officials must bear in mind that more  
38 than one agency may make decisions about partial aspects of a major action. The  
39 following should be considered in evaluating intensity:

- 40 (1) Impacts that may be both beneficial and adverse. A significant effect may exist  
41 even if the federal agency believes that on balance the effect will be beneficial.

- 1 (2) The degree to which the proposed action affects public health or safety.
- 2 (3) Unique characteristics of the geographic area such as proximity to historic or  
3 cultural resources, park lands, prime farmlands, wetlands, wild and scenic rivers,  
4 or ecologically critical areas.
- 5 (4) The degree to which the effects on the quality of the human environment are  
6 likely to be highly controversial.
- 7 (5) The degree to which the possible effects on the human environment are highly  
8 uncertain or involve unique or unknown risks.
- 9 (6) The degree to which the action may establish a precedent for future actions with  
10 significant effects or represents a decision in principle about a future  
11 consideration.
- 12 (7) Whether the action is related to other actions with individually insignificant but  
13 cumulatively significant impacts. Significance exists if it is reasonable to  
14 anticipate a cumulatively significant impact on the environment. Significance  
15 cannot be avoided by terming an action temporary or by breaking it down into  
16 small component parts.
- 17 (8) The degree to which the action may adversely affect districts, sites, highways,  
18 structures, or objects listed in or eligible for listing in the National Register of  
19 Historic Places or may cause loss or destruction of significant scientific, cultural,  
20 or historical resources.
- 21 (9) The degree to which the action may adversely affect an endangered or  
22 threatened species or its habitat that has been determined to be critical under  
23 the Endangered Species Act of 1973.
- 24 (10) Whether the action threatens a violation of federal, state, or local law or  
25 requirements imposed for the protection of the environment.

26 To provide a more conservative analysis, the three counties were selected as the ROI  
27 instead of the EPA-designated Air Quality Control Region, which is a much larger area. Air  
28 quality impacts would be considered significant if the increases in annual emissions of a  
29 pollutant would be anticipated to: (1) cause or contribute to a violation of any national or  
30 state ambient air quality standard; (2) expose sensitive receptors to substantially increased  
31 pollutant concentrations; (3) exceed any evaluation criteria established by an SIP or permit  
32 limitations/requirements; or (4) be anticipated to cause an exceedance of the NAAQS or  
33 contribute to nonattainment.

34 The Air Conformity Applicability Model (ACAM) Version 5.0.7 was utilized to provide a level  
35 of consistency with respect to emissions factors and calculations. The ACAM provides  
36 estimated air emissions from proposed federal actions in areas designated as  
37 nonattainment and/or maintenance for each specific criteria and precursor pollutant as

1 defined in the NAAQS. ACAM was utilized to calculate construction emissions. Emission  
2 factors for aircraft were also obtained from ACAM. Munitions emission factors were used  
3 from EPA's AP-42, Fifth Edition (Volume I, Chapter 15: Ordnance Detonation), and  
4 calculated based on the net weight of the explosive (or a conversion factor for pounds per  
5 item) and the number of times that the munition was used annually. Threat emitter  
6 generator emissions factors were obtained from the *Air Emissions Guide for Air Force  
7 Mobile Sources* (U.S. Air Force, 2016), and calculated based on the horsepower and  
8 annual hours of operation. Equations and emission factors can be found in this appendix.

### 9 **D.1.2.2 Construction Emissions**

10 Calculations for construction emissions were completed using the methodologies  
11 described in the U.S. Air Force *Air Quality Environmental Impact Analysis Process (EIAP)  
12 Guide* (U.S. Air Force, 2016). As previously indicated, Lincoln and Nye Counties are  
13 designated as "attainment", and Clark County was redesignated to maintenance on  
14 November 5, 2014.

15 The ACAM was used to provide a level of consistency with respect to emissions factors  
16 and calculations. The ACAM evaluates the individual emissions from different sources  
17 associated with the construction phases. Phase I is the site preparation phase and  
18 Phase II is the actual construction phase. For emitter pad, roadway, and runway  
19 construction, these sources include grading activities, paving, construction worker trips,  
20 stationary equipment (such as saws and generators), and mobile equipment emissions  
21 (U.S. Air Force, 2014). Formulas and assumptions included in the ACAM program  
22 calculations are provided below in Sections D.1.2.3 through D.1.2.7.

23 Due to limited information, certain assumptions were made to develop the air quality  
24 analysis. It was assumed that there would be a number of 150' by 150' emitter pads  
25 constructed. Analysis calculated the emissions for construction of 15 such pads, to  
26 provide a conservative estimate for the number of pads ultimately constructed and  
27 representative data for various potential increased numbers of emitters. It was further  
28 assumed that for Alternatives 2 and 3, approximately 4 acres of roadway improvements  
29 would be required in order to facilitate installation, maintenance, and potential relocation of  
30 threat emitters and relays. Additionally, under Alternative 3C, it was assumed that surface  
31 improvements of approximately 13 acres would be necessary in order to prepare the  
32 runway to be used in Forward Area Arming and Refueling Points activities.

33 The total square footage of each construction footprint was entered into the ACAM. Based  
34 on these assumptions, the construction emissions were calculated using the methodology  
35 expressed below.

### 36 **D.1.2.3 Grading Activities**

37 Grading activities are divided into grading equipment emissions and grading operations  
38 emissions.

39 Grading equipment emissions are combustive emissions from equipment engines and are  
40 calculated in the following manner:

$$1 \quad \text{VOC} = 0.22 \text{ (lb/acre/day)} * \text{acres} * \text{DPY}_1/2,000$$

$$2 \quad \text{NO}_x = 2.07 \text{ (lb/acre/day)} * \text{acres} * \text{DPY}_1/2,000$$

$$3 \quad \text{PM}_{10} = 0.17 \text{ (lb/acre/day)} * \text{acres} * \text{DPY}_1/2,000$$

$$4 \quad \text{CO} = 0.55 \text{ (lb/acre/day)} * \text{acres} * \text{DPY}_1/2,000$$

$$5 \quad \text{SO}_2 = 0.21 \text{ (lb/acre/day)} * \text{acres} * \text{DPY}_1/2,000$$

6 *Where*

7 acres = number of gross acres to be graded during Phase I construction

8 DPY<sub>1</sub> = number of days per year used for grading during Phase I construction

9 2,000 = conversion factor from pounds to tons

10 All emissions are represented as tons per year.

11 Grading operations emissions are fugitive dust and tiny soil particles distributed into the air  
12 through ground disturbance and are calculated using a similar equation.

13 Emissions calculation:

$$14 \quad \text{PM}_{10} \text{ (tons/yr)} = 60.7 \text{ (lb/acre/day)} * \text{acres} * \text{DPY}_1/2,000$$

15 *Where*

16 acres = number of gross acres to be graded during Phase I construction

17 DPY<sub>1</sub> = number of days per year used for grading during Phase I construction

18 2,000 = conversion factor from pounds to tons

19 The calculations assumed there were no controls used to reduce fugitive emissions. Also,  
20 it was assumed construction activities would occur within a single calendar year to provide  
21 a conservative estimate.

#### 22 **D.1.2.4 Construction Worker Trips**

23 Construction worker trips during the construction phases of the project are calculated and  
24 represented as a function of the number of facilities constructed and/or square feet of  
25 commercial construction.

26 Calculation:

$$27 \quad \text{Trips (trips/day)} = 0.42 \text{ (trip/facility/day)} * \text{Area of training facilities}$$

28 *Where:*

29 Areas of training facilities = total square footage of construction projects to be  
30 constructed in the given year of construction

31 Total daily trips are applied to the following factors depending on the corresponding years.

1 Year 2009:

- 2 •  $VOC_E = 0.016 * \text{trips}$
- 3 •  $NOx_E = 0.015 * \text{trips}$
- 4 •  $PM_{10E} = 0.0022 * \text{trips}$
- 5 •  $CO_E = 0.262 * \text{trips}$

6 Year 2010 and beyond:

- 7 •  $VOC_E = 0.012 * \text{trips}$
- 8 •  $NOx_E = 0.013 * \text{trips}$
- 9 •  $PM_{10E} = 0.0022 * \text{trips}$
- 10 •  $CO_E = 0.262 * \text{trips}$

11 To convert from pounds per day to tons per year:

$$12 \quad VOC \text{ (tons/yr)} = VOC_E * DPY_{II}/2,000$$

$$13 \quad NOx \text{ (tons/yr)} = NOx_E * DPY_{II}/2,000$$

$$14 \quad PM_{10} \text{ (tons/yr)} = PM_{10E} * DPY_{II}/2,000$$

$$15 \quad CO \text{ (tons/yr)} = CO_E * DPY_{II}/2,000$$

16 *Where*

17 2,000 = conversion factor from pounds to tons

18  $DPY_{II}$  = number of days per year during Phase II construction activities

### 19 **D.1.2.5 Stationary Equipment**

20 Emissions from stationary equipment occur when gasoline-powered equipment  
21 (e.g., saws, generators) are used at the construction site.

22 Emissions calculations:

$$23 \quad VOC = 0.198 \text{ pounds (lbs)/day} * (GRSQFT) * DPY_{II}/2,000$$

$$24 \quad NO_x = 0.137 \text{ lbs/day} * (GRSQFT) * DPY_{II}/2,000$$

$$25 \quad PM_{10} = 0.004 \text{ lbs/day} * (GRSQFT) * DPY_{II}/2,000$$

$$26 \quad CO = 5.29 \text{ lbs/day} * (GRSQFT) * DPY_{II}/2,000$$

$$27 \quad SO_2 = 0.007 \text{ lbs/day} * (GRSQFT) * DPY_{II}/2,000$$

28 *Where*

29  $GRSQF$  = gross square feet of commercial buildings to be constructed during Phase  
30 II

31  $DPY_{II}$  = number of days per year during Phase II construction

1           2,000 = conversion factor from pounds to tons

## 2   **D.1.2.6   Mobile Equipment**

3   Mobile equipment (such as forklifts and dump trucks) emissions include pollutant releases  
4   generated by the equipment during Phase II construction.

5   Emissions calculations:

$$6 \qquad \qquad \qquad \text{VOC} = 0.17 \text{ lbs/day} * (\text{GRSQFT}) * \text{DPY}_{\text{II}}/2,000$$

$$7 \qquad \qquad \qquad \text{NO}_x = 1.86 \text{ lbs/day} * (\text{GRSQFT}) * \text{DPY}_{\text{II}}/2,000$$

$$8 \qquad \qquad \qquad \text{PM}_{10} = 0.15 \text{ lbs/day} * (\text{GRSQFT}) * \text{DPY}_{\text{II}}/2,000$$

$$9 \qquad \qquad \qquad \text{CO} = 0.78 \text{ lbs/day} * (\text{GRSQFT}) * \text{DPY}_{\text{II}}/2,000$$

$$10 \qquad \qquad \qquad \text{SO}_2 = 0.23 \text{ lbs/day} * (\text{GRSQFT}) * \text{DPY}_{\text{II}}/2,000$$

11   Where

12           GRSQF = gross square feet of training area to be constructed during Phase II

13           DPY<sub>II</sub> = number of days per year during Phase II construction

14           2,000 = conversion factor from pounds to tons

## 15   **D.1.2.7   Vehicle Emissions**

16   Vehicle emissions are generated from on-road government use, off-road base-support  
17   vehicles, and maintenance construction vehicles.   Since specific numbers and types of  
18   vehicles for each base are difficult to obtain, emissions from this category were based on  
19   historical installation fuel consumption data.

### 20   **D.1.2.7.1   On-Road Government-Owned Vehicle (GOV)**

21   Emissions calculation:

$$22 \qquad \qquad \qquad E_p = N \times F \times \text{GOVMT} \times \frac{EF_p}{454 \times 2000}$$

23   Where

24           N = number of personnel realigned

25           F = fraction of the year the personnel operate

26           GOVMT = per-employee volume of miles traveled (VMT), miles/employee

27           EF<sub>p</sub> = emissions factor for pollutant, *p*, grams/mile.   These factors were determined  
28           from MOVES 2014a for total hydrocarbons (VOCs), CO, and NO<sub>x</sub> for the chosen  
29           fleet mix.

30           454 = conversion factor from grams to pounds



1           2,000 = conversion factor from pounds to tons

#### 2   **D.1.2.7.2 Off-Road Base-Support Vehicles**

3   A variety of off-road base-support vehicles are used at typical Air Force installations.  
4   There are many types of these vehicles, both gasoline and diesel fueled. Since specific  
5   numbers and types of vehicles for each base are difficult to obtain, emissions from this  
6   category were based on historical installation fuel consumption data.

7   Emissions calculation:

$$8 \qquad E_p = N \times F \times \frac{EF_p}{2000}$$

9   *Where*

10           N = number of personnel realigned

11           F = fraction of the year the personnel operate

12           EF<sub>p</sub> = per employee emissions factor, pounds.

13           The emissions factors are as follows:

14           SO<sub>2</sub> = 0.24, PM<sub>10</sub> = 0.34, CO = 7.91, VOC = 0.74

15           2,000 = conversion factor from pounds to tons

#### 16   **D.1.2.8 Aircraft Emissions**

17   Due to limited information, certain assumptions were made to develop the air quality  
18   analysis. The baseline aircraft emissions were calculated using the operations and  
19   scheduling data obtained from operators, schedulers, and air traffic controllers for calendar  
20   year (CY) 2015. This level of activity is assumed representative of an average baseline  
21   year of aircraft operations in NTTR airspace.

##### 22   **D.1.2.8.1 Aircraft Flying Operations**

23   Aircraft operations of concern are those that occur from ground level up to 3,000 feet  
24   above ground level (AGL). The 3,000-foot AGL ceiling was assumed as the atmospheric  
25   mixing height above which any pollutant generated would not contribute to increased  
26   pollutant concentrations at ground level. This is the default value suggested by the EPA in  
27   *Procedures for Emission Inventory Preparation Volume IV: Mobile Sources* (EPA, 1992).  
28   While the *aircraft operation of interest* within the mixing zone is typically the landing and  
29   takeoff (LTO) cycle, because air installation operations are not included in the analysis, the  
30   operations of concern are any low-level testing or training operations that occur below  
31   3,000'.

32   For each mode of operation, an aircraft engine operates at a specified power setting and  
33   for a specific period (time in mode). The pollutant emission rate is a function of the  
34   engine's operating mode, the fuel flow rate, and the engine's overall efficiency. Emissions

1 for a particular aircraft are calculated by knowing the specific engine pollutant emissions  
2 factors for each mode of operation and the time of operation in that mode.

3 The U.S. Air Force has developed emissions factors for aircraft engines, and Table D-6  
4 presents an example of the emissions factors and aircraft engine performance data for  
5 each of the aircraft type used in this analysis. The table lists the various engine modes,  
6 time in for each mode, fuel flow, and corresponding pollutant emissions factors. Using  
7 these data, as well as information on activity levels (i.e., number of sorties/LTO  
8 operations), pollutant emissions for each aircraft were calculated.

9 **Table D-6. Aircraft Performance Data and Emissions Factors**

Aircraft Type	Power Setting	Fuel Flow	VOC	SO <sub>x</sub>	NO <sub>x</sub>	CO	PM <sub>10</sub>	PM <sub>2.5</sub>	CO <sub>2e</sub>
F-16C	Idle	1,006	2.05	1.06	6.21	24.06	2.49	2.24	3,234
	Approach	3,252	0.05	1.06	17.93	1.22	2.37	2.13	3,234
	Intermediate	5,651	0.07	1.06	26.55	0.38	1.58	1.42	3,234
	Military	8,888	0.11	1.06	34.32	0.56	1.58	1.42	3,234
	After Burn	40,122	0.69	1.06	6.63	10.42	3.04	2.74	3,234
F-15E/I	Idle	1,084	7.94	1.06	4.61	35.3	2.06	1.85	3,234
	Approach	3,837	5.12	1.06	12.53	1.92	2.63	2.37	3,234
	Intermediate	5,770	2.89	1.06	22.18	0.86	2.06	1.85	3,234
	Military	96,79	1.79	1.06	29.32	0.86	1.33	1.2	3,234
	After Burn	41,682	1.53	1.06	8.37	11.99	1.15	1.04	3,234

Source: U.S. Air Force, 2016

CO = carbon monoxide; hr = hour; lb = pound; NO<sub>x</sub> = nitrous oxides; PM<sub>10</sub> = particulate matter with an aerodynamic diameter of 10 microns or less; VOC = volatile organic compound

10 Aircraft flying operations were calculated using ACAM emission factors and applying them  
11 to the operational parameters provided by operators in order to calculate the emissions  
12 based on time in mode below 3,000 for each particular aircraft. The operational  
13 parameters used are reflective of the data used for noise analysis. Only those portions of  
14 the flying operation that take place below the atmospheric mixing height are considered  
15 (these are the only emissions presumed to affect ground-level concentrations).

16 Emissions calculation based on aircraft flying operations:

$$17 \quad E_p = N * F * OPS * NUMEG * (\sum TIM_i * E_{Fi,p}) / 2,000$$

18 *Where*

19 N = number of aircraft

20 F = fraction of the year the aircraft operate

21 OPS = the number of operations [total LTOs and touch and go (TGOs)] per year for  
22 each aircraft in the Proposed Action unit

23 TIM<sub>i</sub> = time in mode for aircraft operating mode, *i*, hours

1 The engine operating mode used in the emissions factors is correlated to the aircraft  
 2 operating mode as follows.

- 3 M = number of aircraft operating modes (five for LTOs; three for TGOs)
- 4 NUMEG = the number of engines for the aircraft type
- 5  $E_{Fi,p}$  = emissions factor for pollutant,  $p$ , for each engine operating mode,  $i$ , lb/hr
- 6 2,000 = conversion from pounds to tons

7 Air emissions were estimated for each criteria pollutant based on fuel flow rates for each  
 8 engine mode (e.g., idle, taxi, intermediate, military) per the flight profiles provided by NTTR  
 9 XP. Emissions were then calculated for airspace in the following manner:

10 
$$E_p = (T_{airspace} * (FFR/1000) * E_{Ip})/2000$$

11 *Where*

- 12  $E_p$  = Emissions of pollutant,  $p$ , in tons per year
- 13  $T_{airspace}$  = Time all aircraft in airspace below 3,000 feet AGL (hours per year)
- 14 FFR = Fuel flow rate (pounds per hour)
- 15 1000 = Factor for converting pound per hour to 1,000 pounds per hour
- 16  $E_{Ip}$  = Emission Index for pollutant,  $p$  (pounds per 1,000 pounds of fuel)
- 17 2000 = Factor to convert pounds to tons

18 Airspace units cover large areas of ground and often cover multiple counties. Due to the  
 19 large area and uncertainty of knowing the precise area within any airspace an aircraft may  
 20 be operating, the emissions were compared to a ROI consisting of all counties that  
 21 underlay the airspace.

22 **D.1.2.9 Munition Emissions**

23 Munition emissions for NTTR operations were calculated using similar methodology, using  
 24 operational parameters and munitions quantities consistent with those used for noise  
 25 analysis. Emissions from munitions expended on each of the test areas were calculated  
 26 based on surrogate munitions from each category of munitions expended on the test  
 27 areas. Table D-7 shows the surrogates and the per item emission factors for each munition  
 28 based on its Net Explosive Weight (NEW) used in this analysis.

**Table D-7. Munitions for NTTR Operations Emissions Factors**

Munition Type	Surrogate	DODIC	Emissions Factor (lbs/item)							
			CO	NO <sub>x</sub>	PM <sub>10</sub>	PM <sub>2.5</sub>	SO <sub>x</sub>	VOCs	CO <sub>2</sub>	CH <sub>4</sub>
5.56mm	M855 5.56-mm Ball Cartridge	A059	1.60E-03	8.50E-05	3.90E-05	2.80E-05			7.50E-04	6.70E-06
7.62mm	M80 7.62-mm Ball Cartridge	A143	2.30E-03	9.70E-05	5.10E-05	3.80E-05			1.20E-03	1.00E-05
.50 Caliber	A518, M903 .50 Caliber SLAP Ball	A518	9.60E-03	8.50E-05	2.10E-04	1.80E-04			5.30E-03	8.00E-05

**Table D-7. Munitions for NTTR Operations Emissions Factors**

Munition Type	Surrogate	DODIC	Emissions Factor (lbs/item)							
			CO	NO <sub>x</sub>	PM <sub>10</sub>	PM <sub>2.5</sub>	SO <sub>x</sub>	VOCs	CO <sub>2</sub>	CH <sub>4</sub>
	Cartridge									
.50 Caliber	A557, .50 Cal Ball/Tracer Cart	A557	1.10E-02	1.20E-03	3.10E-04	1.90E-04			5.10E-03	1.30E-04
20mm	A652, M220 20-mm Target Practice Tracer Cartridge	A652	3.30E-02	4.30E-04	6.60E-04	4.60E-04			1.60E-02	2.50E-04
30mm	B129, M789 30-mm High Explosive Dual Purpose Cartridge	B129	8.60E-04	2.00E-04	3.90E-03	2.50E-03			4.40E-03	4.60E-05
40mm	B542, M430 40-mm High Explosive Dual Purpose Cartridge	B542	4.00E-03	1.30E-03	9.50E-03	5.10E-03			4.90E-02	8.90E-05
2.75"	H163, 2.75-inch Rocket with M151 High Explosive Warhead	H163	4.00E-01	5.60E-03	2.40E-01	1.20E-01			7.00E-01	1.20E-02
Bombs	M023, M112 Demo Block Charge	M023	2.10E-02	6.30E-03	2.10E-02	1.50E-02	1.20E-04		6.30E-01	1.30E-03
Bombs	M030, 1/4-lbs Demo Block Chg (TNT)	M030	2.00E-02	1.20E-02	5.00E-02	1.90E-02	3.20E-04		1.40E+00	2.00E-05
Trinitonal Surrogate <sup>1</sup>	Trinitonal	NA	3.98E-03	1.54E-04	3.69E-01	3.69E-01	1.58E-04	2.63E-04	5.25E-01	NA
Signal smoke (BDU)	M4A2 Floating HC Smoke Pot	K867	5.30E-01	2.80E-03	3.00E+01	2.30E+01	3.2s-3	2.20E-02	5.30E-01	NA

Source: EPA, 2009a

CO = carbon monoxide; GBU = guided bomb unit; lb = pounds; mm = millimeter; NEW = net explosive weight; NO<sub>x</sub> = nitrogen oxides; PM<sub>2.5</sub> = particulate matter with an aerodynamic diameter of 2.5 microns or less; PM<sub>10</sub> = particulate matter with an aerodynamic diameter of 10 microns or less; SO<sub>x</sub> = sulfur oxides

<sup>1</sup>Source: U.S. Army, 1996. Characterization of Emissions Produced by the Open Burning/Open Detonation of Complex Munitions.

1 Emissions calculation:

2 
$$\text{Pollutant Emissions} = EF * NEW * Qty / 2,000$$

3 *Where*

4 pollutant emissions = emissions for the associated pollutant (i.e., CO or NO<sub>x</sub>)  
5 (tons/yr)

6 EF = emissions factor for the pollutant (lb/lb NEW)

7 NEW = net explosive weight (lb NEW/item)

8 Qty = quantity (item/year)

9 2,000 = conversion from pounds to tons (1 ton = 2,000 pounds)

### 1 **D.1.2.10 Generator Emissions**

2 Available emissions factors (AP-42, Compilation of Air Pollutant Emission Factors) were  
 3 utilized (EPA, 1996). These factors were then multiplied by the total number of hours of  
 4 operation for each generator by size class. The annual number of pounds of each  
 5 emission was then converted to tons. Annual emissions for each generator were then  
 6 summed to calculate total generator emissions annually.

7 Emissions calculation:

$$8 \quad \text{Emissions} = (HR * EF) / 2000$$

9 *Where:*

10 Emissions = Ordnance Emissions (tons per year)

11 HR = Hours of generator operation per year

12 EF = Emissions factor

13 **Table D-8. Emission Factors for Diesel and Turbine Engines**

Pollutant	Emission Factor (lb/hp-hr)	Emission Factor (LB/MMBtu)
NOx		
Uncontrolled	0.024	3.2
Controlled	0.013	1.9
CO	5.50E-03	0.85
SO <sub>x</sub> <sup>1</sup>	8.09E-03	1.01
CO <sub>2e</sub>	1.16	165
PM	0.0007	0.1
TOC	7.05E-04	0.09
CH <sub>4</sub> <sup>2</sup>	7.05E-04	0.09

Source: EPA, 1996. AP-42, Fifth Edition, Volume I Chapter 3: Stationary Internal  
 Combustion Sources

1 SO<sub>x</sub> mult times S1= % sulfur in fuel oil

2 Based on data from 1 engine, TOC is by weight 9% methane and 91%  
 nonmethane

## 1 D.2 NATIONAL EMISSIONS INVENTORY

2 The NEI is operated under the EPA's Emissions Factor and Inventory Group, which  
3 prepares the national database of air emissions information with input from numerous state  
4 and local air agencies, tribes, and industries. The database contains information on  
5 stationary and mobile sources that emit criteria air pollutants and hazardous air pollutants  
6 (HAPs). The database includes estimates of annual emissions, by source, of air pollutants  
7 in each area of the country on a yearly basis. The NEI includes emissions estimates for all  
8 50 states, the District of Columbia, Puerto Rico, and the Virgin Islands. Emissions  
9 estimates for individual point or major sources (facilities), as well as county-level estimates  
10 for area, mobile, and other sources, are currently from an extract of EPA's NEI database.  
11 The current version of the NEI is the 2014 NEI Database, last updated October 6, 2016.  
12 Data were extracted in October 2016.

13 Criteria air pollutants are those for which the EPA has set health-based standards. Four of  
14 the six criteria pollutants are included in the NEI database:

- 15 • Carbon monoxide (CO)
- 16 • Nitrogen oxides (NO<sub>x</sub>)
- 17 • Sulfur dioxide (SO<sub>2</sub>)
- 18 • Particulate matter (PM<sub>10</sub> and PM<sub>2.5</sub>)

19 The NEI also includes emissions of VOCs, which are ozone precursors, emitted from  
20 motor vehicle fuel distribution and chemical manufacturing, as well as other solvent uses.  
21 VOCs react with nitrogen oxides in the atmosphere to form ozone. The NEI database  
22 defines three classes of criteria air pollutant sources:

23 *Point sources.* Stationary sources of emissions, such as an electric power plant, that can  
24 be identified by name and location. A "major" source emits a threshold amount (or more)  
25 of at least one criteria pollutant and must be inventoried and reported. Many states also  
26 inventory and report stationary sources that emit amounts below the thresholds for each  
27 pollutant.

- 28 • *Area sources.* Small point sources such as a home or office building or a diffuse  
29 stationary source such as wildfires or agricultural tilling. These sources do not  
30 individually produce sufficient emissions to qualify as point sources. Dry cleaners  
31 are one example; for instance, a single dry cleaner within an inventory area typically  
32 will not qualify as a point source, but collectively the emissions from all of the dry  
33 cleaning facilities in the inventory area may be significant and therefore must be  
34 included in the inventory.
- 35 • *Mobile sources.* Any kind of vehicle or equipment with a gasoline or diesel engine  
36 (such as an airplane or ship).

37 The following are the main sources of criteria pollutant emissions data for the NEI:

- 38 • For electric generating units, EPA's Emissions Tracking System/Continuous  
39 Emissions Monitoring Data and Department of Energy fuel use data.

- 1 • For other large stationary sources, state data and older inventories where state data  
2 were not submitted.
- 3 • For on-road mobile sources, the Federal Highway Administration's estimate of  
4 vehicle miles traveled and emissions factors from EPA's MOVES 2014a Model.
- 5 • For non-road mobile sources, EPA's MOVES 2014a Model.
- 6 • For stationary area sources, state data, EPA-developed estimates for some  
7 sources, and older inventories where state or EPA data were not submitted.
- 8 • State and local environmental agencies supply most of the point source data. EPA's  
9 Clean Air Market program supplies emissions data for electric power plants.

## 10 **D.2.1 Greenhouse Gases**

11 GHGs are chemical compounds in the earth's atmosphere that trap heat. Gases exhibiting  
12 greenhouse properties come from both natural and human sources. Water vapor, carbon  
13 dioxide (CO<sub>2</sub>), methane (CH<sub>4</sub>), and nitrous oxide (N<sub>2</sub>O) are examples of GHGs that have  
14 both natural and manmade sources, while other gases such as those used for aerosols are  
15 exclusively manmade. In the United States, GHG emissions come mostly from energy  
16 use. These are driven largely by economic growth, fuel used for electricity generation, and  
17 weather patterns affecting heating and cooling needs.

18 Typically, GHG emissions are represented as CO<sub>2</sub> equivalents (CO<sub>2</sub>e) based on the  
19 molecule's global warming potential or ability to trap heat in the atmosphere relative to CO<sub>2</sub>  
20 (EPA, 2005). Therefore, all GHG emissions calculations and analysis in this document are  
21 represented in CO<sub>2</sub>e.

22 The Air Force has adopted guidance that recommends that any activity that generates  
23 more than 75,000 tons of GHGs is significant. Any GHG analysis contained in this  
24 document was prepared in accordance with the *Air Force Air Quality Environmental Impact*  
25 *Analysis Process (EIAP) Guide – Fundamentals, Volume I and Volume II – Advanced*  
26 *Assessments*. The potential effects of GHG emissions from the Proposed Action are by  
27 nature global. Given the global nature of climate change and the current state of the  
28 science, it is not useful at this time to attempt to link the emissions quantified for local  
29 actions to any specific climatological change or resulting environmental impact.  
30 Nonetheless, the GHG emissions from the No Action Alternative and the Proposed Action  
31 Alternatives have been quantified to the extent feasible in this LEIS for information and  
32 comparative purposes.

### 33 **D.2.1.1 GHG Construction Emissions**

34 Combustion of fossil fuels by construction equipment and constructions workers' vehicles  
35 during commutes to and from the site would contribute to increased GHG emissions.  
36 Construction equipment emits approximately 22.2 pounds of CO<sub>2</sub> per gallon of diesel and  
37 worker vehicles emit 19.4 pounds of CO<sub>2</sub> per gallon of gasoline (EPA, 2009b). These  
38 emission rates can be decreased with less idling and improved maintenance of  
39 equipment. Of 250 potential working days, 90.5 percent (or 238 days) are suitable for  
40 construction activities (i.e., no precipitation greater than 0.10 inches) (National Weather

1 Service, 2016). These vehicles were assumed to each combust 4 gallons of diesel per  
2 hour (Fusetti and Monahan, 2008).

3 Stationary sources for construction were also included in the analysis. It was assumed  
4 that a number of small diesel-fueled generators would be operated during working hours.  
5 Each generator was assumed to combust one gallon per hour of operation.

6 It was assumed that construction workers would be required to commute each day for  
7 238 work days. ACAM estimates the average commute to be 25 miles one-way, and  
8 23.9 miles per gallon average was assumed for commuter vehicles (EPA, 2009b).

### 9 **D.2.1.2 GHG Operational Emissions**

10 Combustion of fuels during flight operations would also cause GHG emissions. Emissions  
11 were calculated using the same methodology and operational parameters as for the  
12 criteria pollutants discussed above. The emissions factors for were also obtained from  
13 ACAM Version 5.0.7. Calculations were based on the estimated annual sorties for each  
14 aircraft under each alternative as discussed above for aircraft criteria pollutant emissions.

15 GHG emissions from munitions use were calculated using emissions factors on a per item  
16 basis as outlined in AP-42 (EPA, 2009a).

---

## 17 **D.3 REFERENCES**

18 Code of Federal Regulations (CFR), Title 40, Part 50 (40 CFR 50). Retrieved from  
19 <http://ecfr.gpoaccess.gov/>.

20 Fusetti, Karin, and Don Monahan, 2008. Technical Memorandum: Mercer Street Greenhouse Gas  
21 Emissions. 19 November 2008.

22 National Weather Service, 2016. Nevada Climatological report (Annual). Accessed online at  
23 <http://w2.weather.gov/climate/getclimate.php?wfo=rev> on November 1, 2016. Nevada  
24 Administrative Code 445B.22907. Standards of Quality for Ambient Air. Last Updated June  
25 2016. Accessed online at <http://www.leg.state.nv.us/nac/nac-445b.html#NAC445BSec22097>  
26 on November 1, 2016.

27 Nevada Division of Environmental Protection (NDEP), 2011. Nevada Air Quality Trend Report  
28 2000-2010. Accessed online at <https://ndep.nv.gov/baqp/monitoring/docs/trend.pdf> on  
29 November 1, 2016.

30 Nevada Division of Environmental Protection (NDEP), 2012a. State of Nevada Applicable State  
31 Implementation Plan Nevada Revised Statutes. NDEP Bureau of Air Quality Protection. Last  
32 revised, November 28, 2012.

33 Nevada Division of Environmental Protection (NDEP), 2012a. State of Nevada Applicable State  
34 Implementation Plan Regulatory Elements: Air Pollution. NDEP Bureau of Air Quality  
35 Protection. Last revised, November 01, 2012.



- 1 O'Brien, R. J., and M. S. Wade, 2003. United States Air Force IERA, Air Emissions Inventory  
2 Guidance Document for Mobile Sources at Air Force Installations. Air Force Institute for  
3 Environment, Safety and Occupational Health Risk Analysis, Risk Analysis Directorate  
4 Environmental Analysis Division, 2513 Kennedy Circle, Brooks AFB, TX 78235. January 2002.  
5 Revised December 2003.
- 6 U.S. Air Force, 2009. Air Force Materiel Command Greenhouse Gas Inventory Guidance Interim.  
7 Prepared for Air Force Center for Engineering and the Environment by CH2M Hill, February  
8 2009.
- 9 U.S. Air Force, 2010b. *Greenhouse Gas Monitoring Plan. Version Number:000*. Prepared by  
10 SAIC. April 1, 2010.
- 11 U.S. Air Force, 2014. U.S. Air Force Air Conformity Applicability Model Quick Start Guide Version  
12 5.0, Air Force Civil Engineer Center. 319 Frank Luke Drive, Bldg. 1438 San Antonio, TX 78226  
13 January 2010.
- 14 U.S. Air Force, 2014a. Nellis AFB, Nevada 2013 Greenhouse Gas Inventory Basewide Summary.
- 15 U.S. Air Force, 2014b. Creech AFB, Nevada 2013 Greenhouse Gas Inventory Basewide Summary.
- 16 U.S. Air Force. 2016. *Air Emissions Guide for Air Force Mobile Sources*. San Antonio, TX: Air  
17 Force Civil Engineer Center.
- 18 U.S. Environmental Protection Agency (EPA), 1992. Procedures for Emission Inventory  
19 Preparation Volume IV Mobile Sources. EPA420-92-009. December 1992.
- 20 U.S. Environmental Protection Agency (EPA), 1996. *AP-42, Fifth Edition, Volume 1 Chapter 3:*  
21 *Gasoline and Diesel Industrial Engines*. Washington, D.C.  
22 <https://www3.epa.gov/ttn/chief/ap42/ch03/final/c03s02.pdf>, retrieved 07 February 2016.
- 23 U.S. Environmental Protection Agency (EPA), 2005. *Emission Facts: Calculating Emissions of*  
24 *Greenhouse Gases: Key Facts and Figures, EPA420-f-05-003*. Washington, D.C.  
25 <http://nepis.epa.gov/Exe/ZyPURL.cgi?Dockey=P1001YTV.txt>, retrieved 11 December 2009.
- 26 U.S. Environmental Protection Agency (EPA), 2009a. *AP-42, Fifth Edition, Volume 1 Chapter 15:*  
27 *Ordnance Detonation*. Washington, D.C. [http://www.epa.gov/ttnchie1/ap42/](http://www.epa.gov/ttnchie1/ap42/ch15/index.html) [ch15/index.html](http://www.epa.gov/ttnchie1/ap42/ch15/index.html),  
28 retrieved 07 February 2016.
- 29 U.S. Environmental Protection Agency (EPA), 2009b. *Inventory of U.S. Greenhouse Gas*  
30 *Emissions and Sinks: 1990-2007, EPA430-R-09-004*. Washington, D.C.  
31 <http://nepis.epa.gov/Exe/ZyNET.exe/P1003A6S.txt>, retrieved 07 February 2010.
- 32 U.S. Environmental Protection Agency (EPA), 2010. *Climate Change – Greenhouse Gas*  
33 *Emissions: In the Home*. Washington, D.C. [http://www.epa.gov/climatechange/](http://www.epa.gov/climatechange/ghgemissions/individual.html)  
34 [ghgemissions/individual.html](http://www.epa.gov/climatechange/ghgemissions/individual.html), retrieved 07 February 2010.
- 35 U.S. Environmental Protection Agency (EPA), 2016. National Ambient Air Quality Standards  
36 (NAAQS), accessed online at <http://epa.gov/air/criteria.html>. July.

This page is intentionally blank.